

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claim 1 (previously amended): A method of receiving data from a network, comprising:

issuing a request directing a transfer of data from one of a plurality of device ports to a storage unit and specifying a thread from among a plurality of processing program threads to process the data.

Claim 2 (previously amended): The method of claim 1, further comprising:
determining if at least one of the plurality of device ports coupled to the network require service.

Claim 3 (previously amended): The method of claim 2, further comprising:
transferring the data to the storage unit and signaling to the specified program thread that the data is ready for processing.

Claim 4 (original): The method of claim 2, wherein determining comprises:
interrogating the plurality of device ports to identify which of the plurality of device ports require service.

Claim 5 (original): The method of claim 4, wherein determining further comprises:
preparing control information corresponding to those device ports identified as requiring service.

Claim 6 (previously amended): The method of claim 5, wherein the control information comprises indicators each associated with a device port receive FIFO in a corresponding one of the device ports.

Claim 7 (previously amended): The method of claim 6, wherein interrogating comprises:

polling the state of the ready flags to determine if the indicators are asserted, the assertion of the indicators indicating that the corresponding device ports have data ready for transfer.

Claim 8 (previously amended): The method of claim 7, wherein the indicators indicate that the associated device port receive FIFO has reached a threshold level of fullness.

Claim 9 (previously amended): The method of claim 8, wherein the indicators indicate that the associated device port receive FIFO stores a full network packet.

Claim 10 (previously amended): The method of claim 5, further comprising:
maintaining a receive ready count, the receive ready count being incremented in response to the control information being prepared.

Claim 11 (original): The method of claim 5, wherein preparing control information further comprises:

writing a flag to a control and status register for each device port in the plurality of device ports that is determined to require service.

Claim 12 (original): The method of claim 11, wherein issuing comprises:
obtaining the control information from the control and status register; and

selecting from each device port in the plurality of device ports having set bits in the control and status register a port for servicing.

Claim 13 (previously amended): The method of claim 1, further comprising:
determining which among the plurality of program threads is available; and
assigning an available program thread to process the data.

Claim 14 (original): The method of claim 12, wherein selecting a port comprises:
using the receive ready count to determine if the ready flags reflect current status of the device port.

Claim 15 (previously amended): The method of claim 3, further comprising:
maintaining a receive request count for counting transfer of data to the storage unit, the receive request count being incremented by one upon the transfer of the data to the storage unit and signaling to the specified program thread.

Claim 16 (previously amended): The method of claim 15, wherein selecting a port further comprises:
using the receive request count to determine if the indicators reflect current status of the device ports.

Claim 17 (previously amended): A method of receiving data from a plurality of peripheral ports, comprising:

determining that the one of the plurality of peripheral ports requires servicing;
issuing a receive request based on the determination, the receive request directing the transfer of data from the one of the plurality of peripheral ports to a buffer memory and specifying a program thread from among of a plurality of processing program threads to process the data; and

transferring the data to the buffer memory and signaling to the specified thread that the data is ready for processing.

Claim 18 (previously amended): An article comprising a computer-readable medium which stores computer-executable instructions for receiving data from a plurality of ports, the instructions causing a computer to:

issue a receive request directing a transfer of data from one of a plurality of device ports to a storage buffer and specifying a program thread from among a plurality of processing program threads to process the data.

Claim 19 (previously amended): The article of claim 18, the article further comprises instructions causing a computer to:

determine if at least one of the plurality of device ports coupled to the network require service.

Claim 20 (previously amended): The article of claim 19, the article further comprises instructions causing a computer to:

transfer the data to the storage unit and signal to the specified program thread that the data is ready for processing.

Claim 21 (original): The article of claim 19, wherein the instructions to determine comprise instructions causing a computer to:

interrogate the plurality of device ports to identify which of the plurality of device ports require service; and

prepare control information corresponding to those device ports identified as requiring service.

Claim 22 (previously amended): The article of claim 21, the article further comprises instructions causing a computer to:

maintain a receive ready count, the receive ready count being incremented in response to the control information being prepared.

Claim 23 (original): The article of claim 22, wherein the instructions to issue comprise instructions causing a computer to:

use the receive ready count to check the current status of the device port.

Claim 24 (previously amended): The article of 19, the article further comprises instructions causing a computer to:

maintain a receive request count for counting transfer of data to the storage unit, the receive request count being incremented by one upon the transfer of the data to the buffer memory and signaling to the specified program thread.

Claim 25 (original): The article of claim 24, wherein the instructions to issue comprise instructions causing a computer to:

use the receive request count to check the current status of the device ports.

Claim 26 (withdrawn).

Claim 27 (withdrawn).

Claim 28 (withdrawn).

Claims 26-43 (withdrawn).

Claim 44 (new). The method of claim 1, wherein the threads comprise threads provided by multiple programmable multi-threaded engines within a processor.